

Mountain Graphic

Website: <http://www.mountaingraphic.com>

Email: mountaingraphic@gmail.com

Phone: 606.335.0375

Fax: 315.693.2971

MAGNETIC CARE

Surface Preparation:

The magnetic sign and surface should be clean and dry. In any outdoor application, such as car signs, the metal surface should be waxed.

Application:

Your magnetic sign holds the best to flat surfaces and surfaces reasonably curved in one direction. When the magnetic is placed in the wrong position, remove magnet and realign. Do not pull the magnet to realign when it is against the surface, as the magnet may stretch due to the resistance caused by the high magnetic strength. Make sure the entire magnet is against the metal surface (no air pockets).

Cleaning:

Some moisture and dirt will collect between the magnet and metal surface, particularly in outside applications (vehicles). Remove and clean both the magnet and surface with mild soap and allow both to dry. On vehicles, repeat the process weekly. To protect the clear coat / base coat and vinyl surfaces present on new vehicles, we recommend daily removal of magnetic signs. We do not recommend applying magnet signs to repainted surfaces.

Storage:

Your magnetic sign is more pliable and easier to work with if it is near room temperature when applied. The best way to store your magnetic is flat, Never magnet to magnet.

We appreciate the trust you have placed in our product. It is our goal to create quality products that meet your expectations.